

Specification Sheet - 110V Non Corrosive Site Light



The high specification non-corrosive fittings have a high ingress protection from moisture, dust, corrosion and vandalism, offering a safer, more efficient alternative to festoon lighting.



2 x 18W
2 x 58W

IP65



Specification

Voltage: 110V
Wattage: 2 x 18W, 2 x 58W
Lamp (not included): T8 fluorescent tubes
Lumen Output: 2000 - 10,000lm
Guarantee: 1 year
IP Rating: IP65
Material: Body made of high impact resistant ABS c/w clear polycarbonate diffuser

Working Temp: -20°C - 60°C

Extra Info:

Body made of high impact resistant ABS c/w clear polycarbonate diffuser
 c/w plastic clips - stainless steel clips available separately.
 High frequency, low power factor ballast.
 3 hour back-up emergency available.
 Standards: F Mark, CE, BS EN60598-2-1 & BS EN60598-2-22.
 Supplied with suspension eye.
 Fittings can be supplied pre-wired with specified lengths of cable and junction box, coupler etc. Please request further information.



MODEL	WATTAGE	LUMEN OUTPUT	EMERGENCY	DIMENSIONS (L x W x D mm)
WF218SV	2 x 18W	2000lm	NO	665 x 155 x 102mm
EW218SV	2 x 18W	2000lm	YES	665 x 155 x 102mm
WF258SV	2 x 58W	10000lm	NO	1586 x 155 x 102mm
EW258SV	2 x 58W	10000lm	YES	1586 x 155 x 102mm

Red Arrow Trading

Elsworth House, Herries Road South
 Sheffield, S6 1QS

T: 0800 195 0006 F: 0870 195 0006

E: sales@redarrowtrading.com www.redarrowtrading.com