## MASHIKO 360 **0550**

# astro

### SKU 1121001



#### PRODUCT SPECIFICATION

#### GENERAL

FINISH:Polished ChromeCABLE LENGTH:Not ApplicableMAIN MATERIAL:Metal - Mild SteelGROSS WEIGHT:1.3 (kg)DIMENSIONS:H: 360mm W: 80mm D: 80mmCLASS:CE (Class II)

INSTALLATION ORIENTATION: Not Applicable IP RATING: IP44

CUT OUT HOLE: Not Applicable BATHROOM ZONE: Zone 2, 3

RECESS DEPTH: Not Applicable VOLTAGE: Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

 LIGHT SOURCE:
 2G11
 MACADAM ELIPSE:
 Not Applicable

 MAXIMUM WATTAGE:
 18W
 UGR:
 Not Applicable

MAXIMUM LAMP LENGTH:Not ApplicableBEAM ANGLE:Not ApplicableLAMP INCLUDED?NoTILT ADJUSTMENT ANGLE:Not Applicable

LUMINOUS FLUX: 453.5 (Im) ROTATION ADJUSTMENT ANGLE: Not Applicable COLOUR TEMP: Lamp Dependent AVERAGE LIFESPAN: 20,000 (Hrs)

CRI: 80 L70: R9: -14.4

ELECTRICAL

SWITCHED:NoSUPPLY FREQUENCY:50/60 (Hz)DIMMABLE:NoDRIVER/BALLAST VOLTAGE:220-240 (V)DIMMING METHOD:Not ApplicableDRIVER AVERAGE LIFESPAN:Not Applicable

DRIVER OUTPUT CURRENT:Not ApplicableEFFICACY:34.86 (lm/W)DRIVER OUTPUT VOLTAGE:Not ApplicableDRIVER/BALLAST INCLUDED?Yes (Integral)

#### ADDITIONAL INFORMATION





This product is not suitable for use with a PIR motion detector.  $\,$ 



BOX QUANTITY X6

Not Applicable

