
## **Cetus LED**



## CU1000ZE4K / 96242099 CETUS LED 1000 HF E3 840




## Cetus LED

A value performance, low height, ceiling recessed LED downlight. Electronic, fixed output control gear with 3 hour, manual test, LED emergency lighting circuit. Body and reflector: aluminium, powder coated white (RAL 9016). Diffuser: polycarbonate. Class I electrical, IP44, IK09. Spring clips suitable for ceiling thicknesses from 1 to 35mm. Cut-out Ø190mm. Complete with 4000K LED.


Dimensions: Ø215 x 88 mm Total power: 12.8 W Weight: 1.75 kg



TLG CTUL F LED.jpg



TLG\_CETU\_M\_E3.wmf



TLG\_SP\_0041866.ldt

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux\*: 1050 lm Total emergency luminous flux: 350 lm

Luminaire efficacy\*: 82 lm/W Lamp efficacy: 82 lm/W

Colour Rendering Index min.: 80 LOR: 1,00 ULOR: 0,00 DLOR: 1,00

Correlated colour temperature\*: 4000 Kelvin

Rated median useful life\*: 50000h L70 at 25°C Ballast: 1x HF\_ Tridonic LCI

Luminaire input power\*: 12.8 W Lambda = 0.95

Charging power: 3.7 W Dimming: Fixed output

Maintenance category: C - Closed Top Reflector

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.