Cetus Mini



96272527 CETUS MINI FH LED550-830 IP20 WH

LED 6W LED_CTUM_540_3K Ta25 IP20 IK 02





Cetus Mini


An economical, fire rated, recessed LED downlight. Integrated phase-cut dimmable control gear. IP20, Class I electrical. Body: steel, painted white. Cover: polycarbonate, red and white. Bezel: aluminium, white. Suitable for mounting in ceiling thicknesses of 13-35mm in a Ø77mm cut-out. Complete with 3000K LED.

Dimensions: Ø87 x 100 mm Total power: 5.7 W


Luminaire luminous flux: 540 lm Luminaire efficacy: 95 lm/W

Weight: 0.5 kg





TLG_CTUM_M_FH.wmf



TLTP_96272527.ldt

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux*: 540 lm Luminaire efficacy*: 95 lm/W Lamp efficacy: 95 lm/W

Colour Rendering Index min.: 80 LOR: 1,00 ULOR: 0,00 DLOR: 1,00 Correlated colour temperature*: 3000 Kelvin Chromaticity tolerance (initial MacAdam)*: 5

Rated median useful life*: 40000h L70 at 25°C

Luminaire input power*: 5.7 W Dimming: PCDCG dimmable to 20% Maintenance category: D - Enclosed IP2X

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of