



TFB3/64 FLOORBOX

Specifications

- Floor box manufactured from galvanised steel
- 20mm KNOCKOUTS ONLY to accept flexible conduit
- Frame & lid moulded from high impact polycarbonate (RAL7031)
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Compact design 303 x 221mm floor cut-out
- Clamp fixing for fast installation
- Large range of accessory plates, colour equivalent: RAL7035
- Available with triple socket accessory plate
- Suitable for carpeted floors only with standard Frame & Lid
- Clean Earth Sockets available
- ABS Plastic Frame & Lid Load Test 550 KG
- Steel Frame & Lid Load Test 740 KG
- **Please note** the 64mm depth floor box has restrictive cabling capacity

Dimensions

Floor Cut Out:	303 x 221mm
Floor Box Depth:	64mm
Plug Top Clearance*:	24mm
Overall Frame & Lid:	313 x 230mm
Frame Lid Recess:	6mm
Accessories Plates:	185 x 89mm

* Be advised that the ST0286 & ST0287 range of accessory plates are not suitable for floorboxes below 80mm depth due to plug top and wiring clearance. For RCD Sockets Please use the TFB3/80 (RCD) Floor box or a deeper floor box.


TFB3/64 Accessory Plates



ST0283
Blank Plate



ST0284
RJ45/LJ6C Plate




* **ST0286**
2x 1 Gang
Accessory Plate




* **ST0287**
Standard Twin
Accessory Plate



ST0289
6x RJ45/LJ6C
Data Plate



ST0291
Twin Switched
Sockets




ST0295
Triple Sockets




* **ST0291/RCD**
Twin RCD
Protected Sockets



ST0294
2x Euro 50x50mm
Plate




* **ST0287/FM**
Flush Standard
Twin Plate




* **ST0286/FM**
Flush Standard
single Plate



ST0284/W
4x RJ45/LJ6C
Wave Plate



ST0291/NSS
2x Non-Standard
Sockets



ST0291/5A
2x 5 Amp Sockets