


Technical Specifications

	EH011	EH010	EH111	EH110	EH171	EG103	EG103E	EG103V	EG203	EG203E	EG493E
Version	Daily	Daily	Daily	Daily	Weekly	Weekly	Weekly	Weekly	Weekly	Weekly	Weekly & Annual
Voltage Supply	230V 50/60Hz	230V 50Hz	230V 50/60Hz	230V 50Hz	230V 50/60Hz	230V AC 50/60Hz	230V AC 50/60Hz	230V AC 50/60Hz	230V AC 50/60Hz	230V AC 50/60Hz	230V AC 50/60Hz
Consumption	0.5VA	0.5VA	0.5VA	0.5VA	0.5VA	6VA	6VA	0.8VA	6VA	6VA	6VA
Output	1 NO Contact Volt Free	1 NO Contact Volt Free	1 C/O Contact Volt Free	1 C/O Contact Volt Free	1 C/O Contact Volt Free	1 Volt Free Changeover Contact	1 Volt Free Changeover Contact	1 Volt Free Changeover Contact	2 Volt Free Changeover Contacts	2 Volt Free Changeover Contacts	2 Volt Free Changeover Contacts 2 NO Contact
Switching Capacity											
AC 1	16A / 250V	16A / 250V	16A / 250V	16A / 250V	16A / 250V	16A AC 1 / 250V 4A DC 1 / 12V	16A AC 1 / 250V 4A DC 1 / 12V	16A AC 1 / 250V 4A DC 1 / 12V	16A AC 1 / 250V 4A DC 1 / 12V	16A AC 1 / 250V 4A DC 1 / 12V	10A AC 1 / 250V
Inductive Load cos 0.6	4A / 250V	4A / 250V	4A / 250V	4A / 250V	2.5A / 250V	10A / 250V	10A / 250V	10A / 250V	10A / 250V	10A / 250V	10A / 250V
Incandescent Lamp	900W	900W	900W	900W	900W	2300W	2300W	2300W	2300W	2300W	1500W
Halogen Lighting 230V	-	-	-	-	-	2300W	2300W	2300W	2300W	2300W	1500W
Compensated Fluorescent Tubes (max 45µF)	-	-	-	-	-	400W	400W	400W	400W	400W	400W
Non Compensated Fluorescent Tubes Compensated in Series	-	-	-	-	-	1000W	1000W	1000W	1000W	1000W	800W
Compact Fluorescent Tubes	-	-	-	-	-	500W	500W	500W	500W	500W	400W
Minimum Current AC 1	-	-	-	-	-	100mA / 250V	100mA / 250V	-	100mA / 250V	100mA / 250V	100mA / 250V
Minimum Current DC 1	-	-	-	-	-	-	-	100mA / 12V	-	-	-
Galvanic Insulation Between Power Supply and Output	-	-	-	-	-	< 4 kV	< 4 kV	< 4 kV	< 4 kV	< 4 kV	< 4 kV
Characteristics											
Technology	Quartz	Quartz	Quartz	Quartz	Quartz	-	-	-	-	-	-
Dial	24hrs	24hrs	24hrs	24hrs	7 days	-	-	-	-	-	-
Minimum Switching	5min	5min	5min	5min	2h	-	-	-	-	-	-
Programming Capacity	-	-	-	-	-	56 Steps	56 Steps	56 Steps	56 Steps	56 Steps	300 Steps
Minimum Time Between 2 Steps	-	-	-	-	-	1min	1min	1min	1min	1min	1min
Working Accuracy	1sec per day	1sec per day	1sec per day	1sec per day	1sec per day	±1.5sec / 24h	±1.5sec / 24h	±1.5sec / 24h	±1.5sec / 24h	±1.5sec / 24h	±0.2sec / 24h
Supply Failure Reserve	200hrs	No	200hrs	No	200hrs	5 years lithium battery	5 years lithium battery	5 years lithium battery	5 years lithium battery	5 years lithium battery	5 Years Lithium Battery
Reached in	120h	120h	120h	120h	120h	-	-	-	-	-	-
Manual Switch Type	On Auto On	Off Auto On	Off Auto On	Off Auto On	Off Auto On	-	-	-	-	-	-
Protection Degree	-	-	-	-	-	IP20	IP20	IP20	IP20	IP20	IP20
Environment											
Working Temperature	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-5°C to +45°C	-5°C to +45°C	-5°C to +45°C	-5°C to +45°C	-5°C to +45°C	-10°C to +45°C
Storage Temperature	-100°C to +50°C	-100°C to +50°C	-100°C to +50°C	-100°C to +50°C	-100°C to +50°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C	-20°C to +70°C
Connection											
Flexible	0.5 to 4mm ²	0.5 to 4mm ²	0.5 to 4mm ²	0.5 to 4mm ²	0.5 to 4mm ²	1.5 to 10mm ²	1.5 to 10mm ²	1.5 to 10mm ²	1.5 to 10mm ²	1.5 to 10mm ²	1 to 4mm ²
Rigid	-	-	-	-	-	1 to 6mm ²	1 to 6mm ²	1 to 6mm ²	1 to 6mm ²	1 to 6mm ²	1.5 to 6mm ²

Modular
Devices

EH010 / EH011
230 VM ±10% 50/60Hz



EH110 / EH111 / EH171
230 VM ±10% 50/60Hz

